


Specifications

Current Rating:0.5A AC/DC
 Voltage Rating:100V AC/DC
 Contact Resistance:40m ohm. Max
 Insulation Resistance:100Mohm min
 Withstanding Voltage:500V(r.m.s) For one Minute
 Operating Temperature Range:-40°C to 105°C
 Materials:
 Insulator:High Temp. Plastic(UL94V-0)
 Color:White
 Contact :Phosphor Bronze
 Plated: Tin Plated

How To Order:

HV08-XX
 HV: Straight Housing
 XX: No. Of Contacts



MATED CONDITION

Pos.	Dim A	Dim B	Dim C	Dim D	Pos.	Dim A	Dim B	Dim C	Dim D
2	0.80	1.78	2.40	3.20	12	8.80	9.78	10.40	11.20
3	1.60	2.58	3.20	4.00	13	9.60	10.58	11.20	12.00
4	2.40	3.38	4.00	4.80	14	10.40	11.38	12.00	12.80
5	3.20	4.18	4.80	5.60	15	11.20	12.18	12.80	13.60
6	4.00	4.98	5.60	6.40	16	12.00	12.98	13.60	14.40
7	4.80	5.78	6.40	7.20	17	12.80	13.78	14.40	15.20
8	5.60	6.58	7.20	8.00	18	13.60	14.58	15.20	16.00
9	6.40	7.38	8.00	8.80	19	14.40	15.38	16.00	16.80
10	7.20	8.18	8.80	9.60	20	15.20	16.18	16.80	17.60
11	8.00	8.98	9.60	10.40					

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:		DESCRIPTION: 0.8mm Housing Straight Type	SIZE A4
E			Ken	.X=±0.20 .XX=±0.15				
D			CHECKED:	UNIT: MM				
C			Lily Chou	SCALE: 1:1				
B			APPROVAL:	SHEET: 1 / 1	PART NO:	HV08-XX		
A	01-SEP-2009	(PC0001)	Ken	Chao Peng	PROJECTION:			
REV	DATE	FILE	BY					