


Specifications:

Current Rating:1.0A AC/DC  
Voltage Rating:30V AC/DC  
Contact Resistance:20m Ohm Max  
Insulation Resistance:1,000M Ohm Min  
Withstanding Voltage:AC 500V AC/Minute  
Operating Temperature Range:-40°C To +105°C  
Mechanical Characteristics  
Mating Force:400gf max.per  
Unmating Force:30gf min.per  
Material and Finish:  
Insulator:High Temp.Plastic(UL94V-0)  
Contact:Copper Alloy  
Finish:Selective Gold Plated  
How To Order  
IDC127-XX-CK



With Bump  
No. Of Positions

Pos	A	B	Pos	A	B
34	25.78	20.32	6	8.00	2.54
40	29.59	24.13	10	10.54	5.08
44	32.13	26.67	12	11.81	6.35
50	35.94	30.48	16	14.35	8.89
60	42.29	36.83	20	16.89	11.43
68	47.37	41.91	26	20.70	15.24
80	54.99	49.53	30	23.24	17.78

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:	<b>HOYATO</b> 东莞好亚通电子厂 Connector supplies	DESCRIPTION:	SIZE
E				Ken	.X=±0.20 .XX=±0.15			
D				CHECKED:	UNIT: MM	DESCRIPTION:	SIZE	
C				Lily Chou	SCALE: 1:1			
B				APPROVAL:	SHEET: 1 / 1	PART NO:	SIZE	
A	01-SEP-2009	(PC0001)	Ken	Chao Peng	PROJECTION:			IDC127-XX-CK
REV	DATE	FILE	BY					