



Specifications:  
 Current rating:1.0A AC,DC  
 Voltage rating:30V AC, DC  
 Contact resistance:20m ohm Max  
 Insulation resistance:1,000M ohm Min  
 Withstanding voltage:500V AC/minute  
 Operating Temperature:-40°C ~ +105°C  
 Material:  
 Insulator:PBT UL94V-0  
 Color:Black  
 Contact:Copper Alloy  
 Plating:Selective Gold Plated

How To Order  
 IDC20-XXSR-XX-XX

- Blank:Black
- BU:Blue
- GR:Gray
- Blank:Without nose
- CK:With nose
- SR:With Strain Relief
- No. of positions

CIRCUITS	DIM.A	DIM.B	DIM.C	CIRCUITS	DIM.A	DIM.B	DIM.C
10	15.34	8.00	9.00	36	41.34	34.00	35.00
12	17.34	10.00	11.00	38	43.34	36.00	37.00
14	19.34	12.00	13.00	40	45.34	38.00	39.00
16	21.34	14.00	15.00	44	49.34	42.00	43.00
18	23.34	16.00	17.00	48	53.34	46.00	47.00
20	25.34	18.00	19.00	50	55.34	48.00	49.00
22	27.34	20.00	21.00	54	59.34	52.00	53.00
24	29.34	22.00	23.00	56	61.34	54.00	55.00
26	31.34	24.00	25.00	60	65.34	58.00	59.00
28	33.34	26.00	27.00	62	67.34	60.00	61.00
30	35.34	28.00	29.00	64	69.34	62.00	63.00
32	37.34	30.00	31.00	68	73.34	66.00	67.00
34	39.34	32.00	33.00				

RoHS Compliant

F				DRAWN: Ken	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15		DESCRIPTION: 2.0MM Flat Cable IDC Socket With Strain Relief	SIZE <b>A4</b>
E								
D				CHECKED: Lily Chou	UNIT: MM	PART NO: IDC20-XXSR-XX-XX		
C					SCALE: 1:1			
B				APPROVAL: Chao Peng	SHEET: 1 / 1			
A	01-SEP-2015	(PC0001)	Ken		PROJECTION:			
REV	DATE	FILE	BY					