

ELANBOON

目录索引 CATALOG INDEX





LVDS

AUTO WIRE HARNESS








WATER-PROOF WIRE

P 07 USB

FLAT CABLE AND WIRE HARNESS P 09-10





LVDS (Low Voltage Differential Signaling, namely low voltage differential signal) interface, also known as RS-644 bus interface, is a data transmission and interface technology proposed only in the 1990s. LVDS interface is a digital video signal transmission mode developed by NS National Semiconductor Company to overcome the disadvantages of high power consumption and high field rate data in TTL level mode. Because of its low pressure and low current drive mode, low noise and low power consumption are achieved. LVDS technology has the characteristics of low power consumption, low error rate, low crosstalk and low radiation. Its transmission medium can be copper PCB connection or balance cable. LVDS has been more and more widely used in the systems with high requirements for signal integrity, low jitter and common modeling, and it is common in LCD TV









FIX40P TO DF13 40P WIRE HARNESS P/N:HCA-HDF125-40-XXXX(Length)

FIX-E 50P*2 TEFELONG WIRE HARNESS P/N:HCA-FIX-50D-XXXX(Length)

P/N:HCA-FIX-40D-XXXX(Length)







P/N:HCA-LVDS-51D-XXXX(Length)

P/N:HCA-LVDS-40D-XXXX(Length)

P/N:HCA-FIX-40D-XXXX(Length)







P/N:CAB-LVDS-30D-XXXX(Length)

P/N:CAB-LVDS-40D-XXXX(Length)

P/N:HCA-SOU-132D-XXXX(Length)







P/N:HCA-SOU-256D-XXXX(Length)

P/N:HCA-H06-12D-XXXX(Length)

P/N:HCA-FX15S-41D-XXXX(Length)







P/N:CAB-LVDS-51D-XXXX(Length)

P/N:CAB-SAS-12D-XXXX(Length)

P/N:CAB-LVDS-30D-XXXX(Length)








P/N:CAB-DF80-50D-XXXX(Length)

P/N:CAB-LVDS-128D-XXXX(Length)

P/N:CAB-IPEX-03D-XXXX(Length)







P/N:CAB-IPEX-30D-XXXX(Length)

P/N:CAB-FPC-24D-XXXX(Length)

P/N:CAB-DF80-40D-XXXX(Length)

Automobile wiring harness is the main body of the network of automobile circuit. Without wiring harness, there is no automotive circuit. Wire harness refers to the contact terminal (connector) made of copper punching and wire and cable compression, after the outside remolding pressure insulation or external metal shell, with wire harness bundle to form a connection circuit components. The wire harness industry chain includes wire and cable, connectors, processing equipment, wire harness manufacturing and downstream application industry, the wire harness is widely used, can be used in automobiles, household appliances, computers and communication equipment, various electronic instruments and other aspects, the body wiring harness connects the whole body









P/N:HCA-HB254-20D-XXXX(Length)

HCA-CAR-AS-XXXX(Length)

P/N:HCA-SHOP-AS-XXXX(Length)









P/N:HCA-SHOP-CAR-XXXX(Length)

P/N:CAB-CBM-20D-XXXX(Length)

P/N:CAB-REL-04D-XXXX(Length)

P/N:CAB-LAMP-02D-XXXX(Length)







P/N:HCA-CAR-08D-XXXX(Length)

HCA-EXC-09D-XXX(Length)

P/N:CAB-LAMP-02-XXXX(Length)

05 蓝博电子