



P2C?B LAYOUT
COMPANENT SIDE

Electric Specifications
 Current Rating:1.1Amps
 Rating Voltage: 250V AC
 Insulation Resistance:100M Ohm Min At DC 500V
 Contact Resistance:30m Ohm Max At DC 100m Amps
 Withstanding Voltage:1 Minute At 750V r.m.s Min
 Temperature Range:-40°C~85°C

Materials:
 Insulator:High Temp. Plastic (Nylon 66 UL94V-0)
 Insulator Color:Black
 Terminal :Copper Alloy
 Plating:Selective Gold Plated

How To Order
 PCIEV10-164G-CK
 — With Central
 — Blank Selective Gold Plated 1u”
 — G5:Selective Gold Plated 5u”
 — No.of Positions
 — Straight Dip Type

RoHS Compliant

REV	DATE	FILE	BY	DRAWN: WGL	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15		DESCRIPTION: PCI-E 164P Straight DIP type With Central Buckle (飞机扣)	SIZE A4
A	17-Mar-2020	(PC0001)	WGL	CHECKED: Jeremy Liu	UNIT: MM SCALE:2:1			
				APPROVAL: Mike Wu	SHEET: 1 / 1			
					PROJECTION:			