



Specifications:
 Current Rating:3.0A AC,DC
 Voltage Rating:250V AC,DC
 Temperature Range:-40°C ~ +85°C
 Contact Resistance:30mohm max.
 Insulation Resistance:5,000Mohm min.
 Withstanding Voltage:1,000V AC/Minute
 Materials:

Insulator:High Temp. Plastic (PBT UL 94V-0)
 Contact:Copper Alloy
 Plating:Gold Plated on Contact Area,
 Tin Plated on Solder Tail.
 Shell:Metal Iron with Nickel plated
 How To Order
 DBSIDC-XX-XX-PSR

Plastic Strain Relief
 BK:Black
 BU:Blue
 No. Of Positions
 S:Socket IDC Type

NUMBER OF POSITIONS	DIMENSION				
	A	B	C	D	E
9	30.80	25.00	16.35	11.08	10.16
15	39.14	33.30	24.75	19.39	17.78
25	53.05	47.04	38.35	33.24	30.48
37	69.32	63.50	54.75	49.86	45.72

RoHS Compliant

E				DRAWN: Jack Zhou
D				CHECKED: Ken Wang
C				APPROVAL: Make Hu
B				
A	20-Mar-2017	(PC0036)	Jack Zhou	
REV	DATE	FILE	BY	

GENERAL TOLERANCE: .X=±0.2 .XX=±0.15
UNIT: MM
SCALE:2:1
SHEET: 1 / 1
PROJECTION:

DESCRIPTION: D-SUB IDC Flat Cable Socket Connector	SIZE
PART NO: DBSIDC-XX-XX-PSR	A4