



铁螺丝 2 PCS

Specifications:
 Current Rating:3.0A AC,DC
 Voltage Rating:250V AC,DC
 Temperature Range:-40°C ~ +85°C
 Contact Resistance:30mohm max.
 Insulation Resistance:5,000Mohm min.
 Withstanding Voltage:1,000V AC/Minute
 Materials:
 Insulator:High Temp. Plastic (PBT UL 94V-0)
 Color:Black
 Contact:Copper Alloy
 Plating:Gold Plated on Contact Area,
 Tin Plated on Solder Tail.
 Shell:Metal Iron with Nickel plated
 How To Order
 DBSRD-XXX-IP

- IPX7
- G:Full Gold plated
- SG:Selective Gold Plated
- No.Of Positions
- R/A Dip
- P:Male

PIN	A	B	C
9	39.40	24.99	16.92
15	47.72	33.32	25.35
25	61.44	47.04	38.96
37	77.9	63.50	55.42

RoHS Compliant

E				DRAWN: Jack Zhou	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15		DESCRIPTION: D-SUB Plug R/A Dip Type	SIZE A4
D				CHECKED: Ken Wang				
C				APPROVAL: Make Hu	SCALE:2:1	PART NO: DBSRD-XXX-IP		
B					SHEET: 1 / 1			PROJECTION:
A	03-Jul-2022	(H0001)	Jack Zhou					
REV	DATE	FILE	BY					