



Specification:  
 Current Rating: 1.0A AC,DC  
 Voltage rating: 125V AC,DC  
 Contact Resistance: 20m Max  
 Insulation Resistance: 100M  
 Withstanding Voltage:250V AC/Minute  
 Temperature Range: -40°C to +85°C  
 Applicable Wire: AWG 28# TO 32#  
 Material:  
 Insulator: High Temp Plastic (Nylon 66 UL94V-0)  
 Insulator Color:Beige

How To Order  
 HSA125-XX  
 No.Of Position  
 Socket Housing

Poles	DIM:(mm)			Poles	DIM:(mm)		
	A	B	C		A	B	C
2	1.25	2.72	5.72	9	10.00	11.47	14.47
3	2.50	3.97	6.97	10	11.25	12.72	15.72
4	3.75	5.22	8.22	11	12.50	13.97	16.97
5	5.00	6.47	9.47	12	13.75	15.22	18.22
6	6.25	7.72	10.72	13	15.00	16.47	19.47
7	7.50	8.97	11.97	14	16.25	17.72	20.72
8	8.75	10.22	13.22	15	17.50	18.97	21.97

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:		DESCRIPTION: 1.25mm Socket Housing	SIZE
E				Ken	.X=±0.20 .XX=±0.15			
D				CHECKED:	UNIT: MM			
C				Lily Chou	SCALE: 1:1			
B				APPROVAL:	SHEET: 1 / 1	PART NO:	HSA125-XX	A4
A	01-SEP-2012	(H0043)	Ken	Chao Peng	PROJECTION:			
REV	DATE	FILE	BY					