


8P~14P Without Guide bulge
16P~40P With Guide bulge

Scale: 1/0.8



Specifications:

Current rating:2.0A AC,DC
Voltage rating:125V AC,DC
Contact resistance:20m ohm.Max
Insulation resistance:1000M ohm.Min
Withstanding voltage:500V AC/minute
Operating temperature range:-40°C~+85°C
Material:
Insulator:Nylon 66 (UL94V-0)
Insulator Color:White

How to Order:

HSD20-XX-LK

└── With Lock

└── No. of Contacts

Poles	Dimensions (mm)				Poles	Dimensions (mm)			
	A	B	C	D		A	B	C	D
2*02	2.00	6.00	4.65	3.55	2*12	22.00	26.00	24.65	23.55
2*03	4.00	8.00	6.65	5.55	2*13	24.00	28.00	26.65	25.55
2*04	6.00	10.00	8.65	7.55	2*14	26.00	30.00	28.65	27.55
2*05	8.00	12.00	10.65	9.55	2*15	28.00	32.00	30.65	29.55
2*06	10.00	14.00	12.65	11.55	2*16	30.00	34.00	32.65	31.55
2*07	12.00	16.00	14.65	13.55	2*17	32.00	36.00	34.65	33.55
2*08	14.00	18.00	16.65	15.55	2*18	34.00	38.00	36.65	35.55
2*09	16.00	20.00	18.65	17.55	2*19	36.00	40.00	38.65	37.55
2*10	18.00	22.00	20.65	19.55	2*20	38.00	42.00	40.65	39.55
2*11	20.00	24.00	22.65	21.55					

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:		DESCRIPTION:	SIZE
E				Ken	.X=±0.20 .XX=±0.15			
D				CHECKED:	UNIT: MM	2.0mm Female Housing With Lock	A4	
C				Lily Chou	SCALE: 1:1			
B				APPROVAL:	SHEET: 1 / 1	PART NO:	HSD20-XX-LK	
A	11-Apr-2021	(PC0001)	Ken	Chao Peng	PROJECTION:			
REV	DATE	FILE	BY					