


PCB CUTOUT PANEL THICKNESS 1.27



eSpecifications:

Current Rating:7.0A AC/DC
 Voltage Rating:600V AC/DC
 Contact Resistance:10M Ohm. Max.
 Insulation Resistance:1,000M Ohm. Min.
 Withstanding Voltage:1500V AC/Minute
 Operating Temperature Range:-25°C ~ +85°C

Material And Finish:

Insulator:Nylon 66 (UL94V-2)
 Color:Transparent White
 Contact:Brass
 Finish:Nickel Plated
 How To Order
 HSD42-XX-XX-SP

— Screw Propeller
 — Blank :White
 — BK:Black
 — No. of Positions

Part No	Dimensions (mm)							
	A	B	C	D	E	F	G	H
2x01	36.00		25.00	25.00	13.40	10.10	8.70	5.40
2x02	40.20	4.20	29.20	29.20	17.60	14.30	12.90	9.60
2x03	44.40	8.40	33.40	33.40	21.80	18.50	17.10	13.80
2x04	48.60	12.60	37.60	37.60	26.00	22.70	21.30	18.00
2x05	52.80	16.80	41.80	41.80	30.20	26.90	25.50	22.20
2x06	57.00	21.00	46.00	46.00	34.40	31.10	29.70	26.40
2x07	61.20	25.20	50.20	50.20	38.60	35.30	33.90	30.60
2x08	65.40	29.40	54.40	54.40	42.80	39.50	38.10	34.80
2x09	69.60	33.60	58.60	58.60	47.00	43.70	42.30	39.00
2x10	73.80	37.80	62.80	62.80	51.20	47.90	46.50	43.20
2x11	78.00	42.00	67.00	67.00	55.40	52.10	50.70	47.40
2x12	82.20	46.20	71.20	71.20	59.60	56.30	54.90	51.60

F			
E			
D			
C			
B			
A	01-SEP-2017	(PC0001)	Ken
REV	DATE	FILE	BY

DRAWN: Ken	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15
CHECKED: Lily Chou	
APPROVAL: Chao Peng	
UNIT: MM SCALE: 1:2 SHEET: 1 / 2 PROJECTION:	

	DESCRIPTION: 4.2mm Mini Fit Double Row Female Housing & Terminal	SIZE A4
	PART NO: HSD42-XX-XX-SP	