



Specifications:

Current rating:1.0A AC/DC
 Voltage rating:30V AC/DC
 Contact resistance:20m ohm max.
 Withstanding Voltage:500V AC/minute
 Insulation resistance:1000M ohm min.
 Temperature Rating:-40°C ~ +105°C
 Materials:

Insulator:PBT(UL94V-0)
 Contact:Copper Alloy
 Finish:Selective Gold Plated

How To Order
 IDC254-XXSR-XX



Dimension Information:

Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B
6	12.30	5.08	30	42.78	35.56
8	14.84	7.62	34	47.86	40.64
10	17.38	10.16	36	50.40	43.18
12	19.92	12.70	40	55.48	48.26
14	22.46	15.24	44	60.56	53.34
16	25.00	17.78	50	68.18	60.96
18	27.54	20.32	56	75.80	68.58
20	30.08	22.86	60	80.88	73.66
24	35.16	27.94	64	85.96	78.74
26	37.70	30.48			

RoHS Compliant

F				DRAWN: Ken	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	HOYATO 东莞好亚通电子厂 Connector supplies	DESCRIPTION: 2.54MM Flat Cable IDC Socket With Strain Relief	SIZE A4
E			CHECKED: Lily Chou					
D				APPROVAL: Chao Peng	SCALE: 1:1	PART NO: IDC254-XXSR-XX		
C					SHEET: 1 / 1			
B					PROJECTION:			
A	01-SEP-2009	(PC0001)	Ken					
REV	DATE	FILE	BY					