


Specifications:

Current Rating:1.0A AC/DC  
 Voltage Rating:30V AC/DC  
 Contact Resistance:20m ohm. Max.  
 Insulation Resistance:100M ohm. Min .  
 Withstanding Voltage:250V AC For One Minute  
 Operating Temperature Range:-40°C to +105°C  
 Material and Finish  
 Insulator:PBT (UL94V-0)  
 Insulator Color:Black  
 Contact:Phosphor Bronze  
 Contact Plating:Selective Gold Plated  
 Shell:Brass Nickel Plated

How To Order

MDS-XX-4M



Circuits	3	4	5	6	7	8
Arrangement of Contact						
RECOMMENDED P.C.B LAYOUT (TOLERANCE:±0.05)						

RoHS Compliant

F				DRAWN: Ken	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15		DESCRIPTION: Mini Din JACK PCB Type R/A Entry	SIZE <b>A4</b>
E								
D				CHECKED: Lily Chou	UNIT: MM	PART NO: MCS-XX-4M		
C					SCALE: 1:1			
B				APPROVAL: Chao Peng	SHEET: 1 / 1	PROJECTION:		
A	05-Apr-2017	(PC0001)	Ken					
REV	DATE	FILE	BY					