



Specifications:
 Current Rating:1.0A AC,DC
 Voltage Rating:30V AC,DC
 Contact Resistance:20M Ohm Max
 Insulation Resistance:1,000M Ohm Min
 Withstanding Voltage:750V AC/Minute
 Operating Temperature Range:-40°C to +105°C
 Materials:
 Insulator:High Temp.Plastic (LCP UL94V-0)
 Contact:Brass
 Plating:Gold Plated on Contact Area,
 Tin Plated on Solder Tail.
 Shell:SPCC,Tin Plate

OVAL RING
 1. The amount of low molecular siloxanes(D3~D10)is
 2. Hardness of silicone rubber:70°
 3. Horizontal flash 0.1max;Longitudinal flash 0.10max
 BODY WITH O-RING'S SFAL ARFA BURRS IS 0.05mm Max

How To Order
 MUBPRSM1-05IP
 IPX7
 No. Of Positions
 Micro USB Plug

RoHS Compliant

E				
D				
C				
B	26-Jun-2019	add Plug Mating View	Jack Zhou	
A	28-Oct-2015	(H0001)	Jack Zhou	
REV	DATE	FILE	BY	

DRAWN: Jack Zhou	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15
CHECKED: Ken Wang	UNIT: MM
APPROVAL: Make Hu	SCALE:2:1
	SHEET: 1 / 1
	PROJECTION:

DESCRIPTION: Micro USB Plug 5P SMT Type	SIZE A4
PART NO: MUBPRSM1-05IP	